

WAGNER

Accessories

Perfect for all concrete repair jobs	Part no.
Spray gun AG 14 (stainless steel)	0502 166
Spray gun AG 08 (aluminium made) (01)	0296 388
Whip hose (02)	97 057
HP ball cock with slide coupling (03)	2353 775
HP ball cock with mouth piece (04)	2353 754
HP ball cock with whip hose and slide coupling	2353 789
HP ball cock with whip hose and mouth piece (05)	2353 788
Hopper 5l	2357 506
Pressure measuring unit 400 bar (06)	2353 487
HP hose DN6; 6 m; steel-reinforced; for injection work	2351 983
HP hose DN6; 15 m; textile-reinforced; for paint spraying	9984 574

01



02



03



04



05



06



Printed in Germany - Subject to modifications - EN - 23.62.322 - 08/2015 IM

WAGNER

SuperFinish 23i

NEW



PROFESSIONAL CRACK INJECTION

Precise, user-friendly and efficient in filling and redevelopment



Our quality assures you. That's a promise.

Everyone who buys a WAGNER paint sprayer always receives a three-year manufacturer's warranty. However, we can offer more by registering online, you can extend the warranty by a further two years, free of charge!

www.wagner-group.com/professional-guarantee



FOR PRECISE CONCRETE REPAIR AND INJECTION

Powerful diaphragm pump: big diaphragm surface for perfect usage with high viscosity materials and a long life time

Variety of materials: suitable for Epoxy and Polyurethanes (PU), SPUR foam, aqueous solutions

Because it's so easy: service, cleaning and maintenance directly on the job site is no problem at all

Well-arranged: handy pressure regulation in low pressure areas (starting from 10-20 bar)

TECHNICAL DATA

Voltage 230 V / 50 Hz

Power input 1.3 kW

Max. operating pressure 25 MPa (250 bar)


Max. conveying performance 2.6 l/min

Weight on carriage 29 kg

Part no. basic unit 2357 691

Part no. basic unit with hopper and pressure gauge 2361 599

Please check last page for accessories



The intake valve button
ensures high operational safety - Just the press of a thumb, and the valve is free

Precise injection
Easy to use with all packings commercially available

Easy to clean:
5 litre hopper for quick material changeovers and small quantities processing

Easy transport
Stable cart with pole adjustable in height

Pressure relief valve directly on the device
Return ball valve specifically for injection applications

Brushless motor
Maintenance-free and total reliability

Large variety of materials with QLS long-stroke technology:
The optimised hydraulics and special valve technology make it possible

Temperature sensitive
Low-temperature pump head, cools the device in operation

Ease of use
Infinitely variable pressure regulation from 0 to 3600 PSI

Illustration incl. accessories, isn't equal to scope of delivery

