

**Convertible Petrol/Electric Airless Paint Sprayers**



# **PowerTwin<sup>TM</sup>** **XLT** *Series*



***When Reliability Counts!***



*Global Leader in Paint  
Spray Technology*

# PowrTwin XLT FEATURES

*The Contractor's Choice for Big Projects!*

## **PowrTwin™ XLT**

*When Reliability Counts!*



*Speeflo is the world's most popular manufacturer of hydraulic paint sprayers.*

*PowrTwin XLT models are perfect for interior and exterior work. They convert quickly from petrol to electric and are easy for one person to transport to the job and on the job. PowrTwins are powerful enough to spray the most difficult architectural and commercial coatings.*

*Proven reliable and easy to maintain...*

*Speeflo is the only sprayer you will ever need!*

### **1 HydraDrive™**

- Mechanical valve eliminates expensive electronic switching devices.
- External Hydraulic Fluid Porting with new and upgraded fittings, allow for quick trouble shooting and easy maintenance.
- Precision rod alignment for maximum chrome life.
- SAE O-Ring fitting for precision alignment.

### **2 Converts from Petrol to Electric**

- Change from petrol to electric or vice versa in seconds – without tools. Never miss a job because you don't have the right power. Use the petrol engine on exteriors or switch to electric for inside jobs. *Your PowrTwin keeps your crew on the job making you money.*

**230 V Convertokit**



**Honda Engine**



**120 V Convertokit**

**3**



### **Hydraulic Fill and Dip Stick**

- Easy access equals less mess
- Sturdy metal dip stick

**4**



### **High Capacity Hydraulic Fluid Cartridge Filter**

- Keeps hydraulic system clean and easy to maintain

**5**



### **Heavy Duty Paint Filter**

- Longer tip life
- Increased productivity



### **6 Coolflo™ Hydraulic Pump**

- Runs cool
- No clutch to wear
- No routine maintenance

### **7 Hydraulic Fluid Reservoir**

- Compact and lightweight for maximum portability and heat dissipation



## ***XLTDI Models*** Direct Immersion

	<b>PowrTwin™ 6900XLTDI</b>	<b>PowrTwin™ 12000XLTDI</b>
Electric 230 V Model w/ S-5 Gun, Tip, and 3/8" Hose Kit & Heavy Duty Bypass Valve	448-370	N/A
Petrol Model w/ S-5 Gun, Tip, and 3/8" Hose Kit	N/A	459-355
Petrol Model w/ S-5 Gun, Tip, and 3/8" Hose Kit & Heavy Duty Bypass Valve	448-360	N/A
<b>Petrol Engine</b>	4 kW (5.5 hp) Honda	7 kW (9 hp) Honda
<b>Max. Tip Size - Petrol</b>	1 gun - 1.22 mm (.048")	1 gun - 1.47 mm (.058")
<i>Maximum tip sizes vary with materials sprayed</i>	2 guns - .84 mm (.033")	2 guns - 1.02 mm (.040")
	3 guns - .58mm (.023")	3 guns - .86 mm (.034")
	4 guns - .48 mm (.019")	4 guns - .76 mm (.030")
		5 guns - .66 mm (.026")
		6 guns - .61 mm (.024")
<b>Max. Tip Size - Electric</b>	1 gun - .91 mm (.036")	1 gun - .91 mm (.036")
	2 guns - .66 mm (.026")	2 guns - .66 mm (.026")
	3 guns - .48 mm (.019")	3 guns - .48 mm (.019")
<b>Max. Output - Petrol</b>	8.14 lpm (2.15 gpm)	11.9 lpm (3.15 gpm)
<b>Max. Output - Electric</b>	4.73 lpm (1.25 gpm)	4.73 lpm (1.25 gpm)
<b>Max. Operating Pressure</b>	228 bar (3,300 psi)	228 bar (3,300 psi)
<b>Cycles Per Liter</b>	14 L (55 gal)	10 L (40 gal)
<b>Paint Outlet Filter</b>	5 mesh	5 mesh
<b>Filter Area</b>	115 cm² (18 in²)	115 cm² (18 in²)
<b>Frame</b>	EZ-Load Swing-In	EZ-Load Swing-In
<b>Sprayer Dimensions</b>	109 cm H x 69 cm W x 89 cm L 43" (L) x 27" (W) x 35" (H)	117 cm H x 69 cm W x 89 cm L 46" (L) x 27" (W) x 35" (H)
<b>Sprayer Weight - Petrol</b>	67.6 kgs (149 lbs)	85.3 kgs (188 lbs)
<b>Sprayer Weight - Electric</b>	74.8 kgs (165 lbs)	87.1 kgs (192 lbs)
<b>Honda Petrol Convertokit</b>	506-275	506-277
<b>Exl-DC Electric Convertokit 110-120 V</b>	506-279	506-279
<b>DC Electric Convertokit 230 V</b>	506-251	506-251

*The PowrTwin XLTDI series are designed specifically for airless spray fillers. These extremely powerful machines are also ideal for spraying latex, solvent and emulsion paints.*





## **XLT Models** Siphon Hose Feed

	<b>PowrTwin™ 4900XLT</b>	<b>PowrTwin™ 6900XLT</b>	<b>PowrTwin™ 8900XLT</b>	<b>PowrTwin™ 12000XLT</b>
<b>Electric 230 V Model w/ LX-80° Gun, Tip, and 1/4" Hose Kit</b>	335-325	448-325	N/A	N/A
<b>Petrol Model w/ LX-80° Gun, Tip, and 1/4" Hose Kit</b>	335-315	448-315	N/A	N/A
<b>Petrol Model w/ S-5 Gun, Tip, and 1/4" Hose Kit</b>	N/A	N/A	449-315	459-315
<b>Petrol Engine</b>	3 kW (4 hp) Honda	4 kW (5.5 hp) Honda	5 kW (6.5 hp) Honda	7 kW (9 hp) Honda
<b>Electric Motor</b>	1.5 kW (2 hp) Ext. Life-DC	1.5 kW (2 hp) Ext. Life-DC	1.5 kW (2 hp) Ext. Life-DC	1.5 kW (2 hp) Ext. Life-DC
<b>Max. Tip Size - Petrol</b>	1 gun - .91 mm (.036") 2 guns - .71 mm (.028") 3 guns - .56 mm (.022")	1 gun - 1.22 mm (.048") 2 guns - .84 mm (.033") 3 guns - .58 mm (.023") 4 guns - .48 mm (.019")	1 gun - 1.32 mm (.052") 2 guns - .97 mm (.038") 3 guns - .81 mm (.032") 4 guns - .71 mm (.028") 5 guns - .61 mm (.024")	1 gun - 1.47 mm (.058") 2 guns - 1.02 mm (.040") 3 guns - .86 mm (.034") 4 guns - .76 mm (.030") 5 guns - .66 mm (.026") 6 guns - .61 mm (.024")
<i>Maximum tip sizes vary with materials sprayed</i>				
<b>Max. Tip Size - Electric</b>	1 gun - .78 mm (.031") 2 guns - .58 mm (.023") 3 guns - .48 mm (.019")	1 gun - .91 mm (.036") 2 guns - .66 mm (.026") 3 guns - .48 mm (.019")	1 gun - .91 mm (.036") 2 guns - .66 mm (.026") 3 guns - .48 mm (.019")	1 gun - .91 mm (.036") 2 guns - .66 mm (.026") 3 guns - .48 mm (.019")
<b>Max. Output - Petrol</b>	4.73 lpm (1.25 gpm)	8.14 lpm (2.15 gpm)	8.9 lpm (2.35 gpm)	11.9 lpm (3.15 gpm)
<b>Max. Output - Electric</b>	4.16 lpm (1.10 gpm)	4.73 lpm (1.25 gpm)	4.73 lpm (1.25 gpm)	4.73 lpm (1.25 gpm)
<b>Max. Operating Pressure</b>	228 bar (3,300 psi)	228 bar (3,300 psi)	228 bar (3,300 psi)	228 bar (3,300 psi)
<b>Cycles Per Liter</b>	23 L (87 gal)	14 L (55 gal)	10 L (40 gal)	10 L (40 gal)
<b>Paint Outlet Filter</b>	50 mesh	50 mesh	50 mesh	50 mesh
<b>Filter Area</b>	115 cm² (18 in²)	115 cm² (18 in²)	115 cm² (18 in²)	115 cm² (18 in²)
<b>Frame</b>	EZ-Load Compact	EZ-Load Compact	EZ-Load H.D.	EZ-Load H.D.
<b>Sprayer Dimensions</b>	94 cm H x 69 cm W x 89 cm L 37" (L) x 27" (W) x 35" (H)	94 cm H x 69 cm W x 89 cm L 37" (L) x 27" (W) x 35" (H)	109 cm H x 69 cm W x 89 cm L 43" (L) x 27" (W) x 35" (H)	117 cm H x 69 cm W x 89 cm L 46" (L) x 27" (W) x 35" (H)
<b>Sprayer Weight - Petrol</b>	59 kgs (130 lbs)	63.1 kgs (139 lbs)	70.3 kgs (155 lbs)	82.6 kgs (182 lbs)
<b>Sprayer Weight - Electric</b>	63.1 kgs (139 lbs)	67.1 kgs (148 lbs)	74.4 kgs (164 lbs)	85.3 kgs (188 lbs)
<b>Honda Petrol Convertokit</b>	506-112	506-275	506-278	506-277
<b>Exl-DC Electric Convertokit 110-120 V</b>	506-217	506-211	506-276	506-207
<b>DC Electric Convertokit 230 V</b>	506-252	506-251	506-251	506-251

*The **PowrTwin XLT** series are designed for large building projects. They have the ability to use multiple guns from one **PowrTwin XLT** sprayer.*





### Accutrol™ Pressure Control

- Accurate from 28 bar up to 227 bar
- No electronics
- No freeze hazard
- No maintenance



### High Efficiency Cooling Fan

- Keeps the hydraulics cooler for longer life



### Durable, Chrome Plated Cart

- Telescoping handle and lift handle for easy loading

### Large Pneumatic Tyres

- Large pneumatic tyres for ease of transportation, even in the most severe job-site conditions

### Foot Valve

- Submersed lower foot valve allows for siphoning of ultra heavy coatings and knockdown textures (PowrTwin 6900DI only).



### EZ-Swing Frame

- Allows for less spillage during paint changes
- Lowers height of unit for easier transportation

# ACCESSORIES

**SC-6  
TIP**



- The Longest Lasting Tip in the Industry.
- Universal size to fit most bases.
- Fewer passes and better coverage than competitors because of full fan pattern with minimal feathering.
- New one-piece seal and retainer.

**Product No. 661-XXX**



**SYNERGY  
FINE-FINISH TIP**

**Product No. 671-XXX**

**WIDESPRAY™**

**Product No. 661-XXXX**



SC-6 Reversible Tip Guard . . . . .	661-012
S5 Gun w/SC-6 Tip . . . . .	550-100
S3 Gun w/SC-6 Tip . . . . .	550-250
L70 Inline Gun . . . . .	550-475
LX-80 <sup>II</sup> Gun w/SC-6 Tip . . . . .	580-100
Reel-EZ 16 – 406 mm (16”) Hose Reel. . . . .	769-100
Reel-EZ 10 – 254 mm (10”) Hose Reel. . . . .	769-200
LX 75 Pole Gun 120 cm (47.2”) . . . . .	550-495
Tip Extension 15 cm (6”) 7/8 THD. . . . .	651-070
Tip Extension 30 cm (12”) 7/8 THD. . . . .	651-071
Tip Extension 45 cm (18”) 7/8 THD. . . . .	651-072
Tip Extension 61 cm (24”) 7/8 THD. . . . .	651-073
Tip Extension 15 cm (6”) 11/16 THD. . . . .	651-121
Tip Extension 30 cm (12”) 11/16 THD. . . . .	651-122
Tip Extension 45 cm (18”) 11/16 THD. . . . .	651-123
Tip Extension 61 cm (24”) 11/16 THD. . . . .	651-124
90 cm (3’) Extension Pole w/Swivel Head, 7/8 Nut. . . . .	310-390
180 cm (6’) Extension Pole w/Swivel Head, 7/8 Nut. . . . .	310-391
Gun Extension Swivel Head, 7/8 . . . . .	651-139
Gun Extension Swivel Head, 11/16 . . . . .	651-140

Spray/Roll Application Kit. . . . .	310-110
229 mm (9”) Telescoping Pressure Roller Kit. . . . .	310-950
6.35 mm (1/4”) x 15.2 m (50’) Airless Hose, 228 bar . . . . .	316-505
4.76 mm (3/16”) x .91 m (3’) Airless Whip Hose . . . . .	550-240
Fine Mesh Gun Filter (Pack of 2) . . . . .	500-200-10
Medium Mesh Gun Filter (Pack of 2) . . . . .	500-200-06
Coarse Mesh 440i Manifold Filter (Pack of 2) . . . . .	500-200-03
Medium Mesh 640i Manifold Filter . . . . .	730-067
Inlet Screen for STD PowrTwins . . . . .	103-627
Manifold Filter Mastic - 0 Mesh . . . . .	930-004
Manifold Filter Mastic - 5 Mesh . . . . .	930-005
Manifold Filter Mastic - 50 Mesh . . . . .	930-006
Manifold Filter Mastic - 100 Mesh . . . . .	930-007
Large Inlet Screen (Rock Catcher) DI. . . . .	710-046
3.175 mm (1/8”) Airless Tip Gaskets (12 Gaskets) . . . . .	711-612
Piston Lube - 237 mL (8 oz.) Bottle . . . . .	314-480
Piston Lube - 118 mL (4 oz.) Bottle . . . . .	314-481
LS-10 Liquid Shield Plus - .95 L (1 Qt.) Bottle . . . . .	314-482
LS-10 Liquid Shield Plus - 118 mL (4 oz.) Bottle . . . . .	314-483

Imported by:

Distributed by:

## International Sales

*Titan Tool, Inc.*

**Tel: +201.405.7480**

**Fax: +201.405.7449**

*Distribution Center*

**1770 Fernbrook Lane**

**Plymouth, MN 55447 – USA**

## Ask for Genuine Titan/Speeflo Parts and Accessories



*Global Leader in Paint  
Spray Technology*



**Website: [www.titantool.com/international](http://www.titantool.com/international)**



©Copyright 2008 Titan Tool, Inc. Titan and Speeflo are registered trademarks and PowrTwin, ExL DC Motor, ConvertoKit, Accutrol, SC-6 Tip and Severe Service 900 are trademarks of Titan Tool, Inc.  
JB50349B SL 40000 / 02-2007